


01

**Termoventilatore ceramico digitale**  
Digital ceramic fan heater

NEW




**Display a LED, tasti soft touch**  
LED display, soft touch keys



**Base oscillante, per una distribuzione ottimale dell'aria in ambiente**  
Oscillating base, for optimal air distribution in the environment



**Telecomando slim**  
Slim remote control



**Dimensioni**  
Dimensions

# ARGO BOBO

191070210

Il bianco totale ne valorizza il design minimal ma estremamente curato. Il pannello comandi è a sfioro e si illumina al tocco, per poi spegnersi se non utilizzato. L'oscillazione orizzontale, gestibile sia da pannello che da telecomando, garantisce la distribuzione ottimale dell'aria in ambiente.

The total white enhances the minimal but extremely refined design. The control panel is touch sensitive and it lights up when touched, and then turns off if not used. The horizontal oscillation, which can be managed both from the panel and from the remote control, guarantees optimal distribution of the air in the room.



## DESIGN TECNOLOGICO

- > Design minimal, lineare, total white
- > Finitura matt di colore bianco puro
- > Da posizionare su un tavolo o a pavimento
- > Pannello comandi soft touch
- > Display a LED bianchi
- > Luminosità del display regolabile a step 100%, 50%, 25% o OFF
- > Riduzione automatica della luminosità al 50% dopo 1 minuto
- > LED luminosi per impostazione:
  - 6 step di regolazione della temperatura: 10-15-20-23-27-30 °C
  - timer di funzionamento: 1-9 ore
  - 2 livelli di potenza: 1350/2000 W
- > Modalità ventilazione fredda
- > Modalità di riscaldamento: ECO/COMFORT
- > Dispositivo anti-ribaltamento
- > Doppia protezione anti-surriscaldamento
- > Telecomando slim per il controllo delle funzionalità

## TECHNOLOGICAL DESIGN

- > Minimal, linear, total white design
- > Matt finish in pure white color
- > To be placed on a table or on the floor
- > Soft touch control panel
- > White LED display
- > Display brightness adjustable by steps of 100%, 50%, 25% or OFF
- > Automatic brightness reduction to 50% after 1 minute
- > Bright LEDs for setting:
  - 6 temperature adjustment steps: 10-15-20-23-27-30 °C
  - operating timer: 1-9 hours
  - 2 power levels: 1350/2000 W
- > Cool ventilation mode
- > Heating modes: ECO/COMFORT
- > Anti-tilting device
- > Double overheating protection
- > Slim remote control for functional control

EAN 8013557519101

MODELLO / MODEL		ARGO BOBO
Funzioni speciali - applicazioni / Special function - applications		Display a LED con regolazione della luminosità e oscillazione della base / LED display with brightness adjustment and base swinging
Modalità di riscaldamento / Heating modes		ECO/COMFORT
Modalità di riscaldamento - livelli di potenza / Heating modes - power levels	no.	2
Potenza riscaldamento max. / Max. heating capacity	W	2000
Volume riscaldabile / Heating volume	m <sup>3</sup>	60
Timer di spegnimento / Switch off timer		1-9h
Filtro anti-polvere lavabile / Washable anti-dust filter		•
Apparecchio portatile / Portable unit		•
Doppio isolamento elettrico / Double electrical insulation		•
Termostato digitale / Digital thermostat	°C	10-30
Ventilazione forzata / Forced ventilation		•
Oscillazione orizzontale / Horizontal swinging		•
Resistenza ceramica / Ceramic heating element		•
Tensione di alimentazione / Power supply	V/Ph/Hz	220-240~/1/50-60
Potenza assorbita (min./max.) / Power input (min./max.)	W	1350/2000
Protezione PTC / PTC protection		•
Dispositivo antisurriscaldamento / Overheating safety device		•
Dispositivo antiribaltamento / Anti-tipping safety device		•
Dimensioni (Alt./Lar./Pro.) / Dimensions (H./W./D.)	mm	385/175/128
Peso / Weight	kg	2,1